


REV	ECN NO	DESCRIPTION	DATE	APPROVED
AA	-	NEW RELEASED	2015. 12. 01	CLARA



Connector Table 1


Bomcan Part No.	Coding & Pins	Socket Pin out	Contact Size(mm)	Rated Current	Rated Voltage
M09A02SM01ST	A Code 2 Pin		1.0	4A	125V
M09A03SM01ST	A Code 3 Pin		1.0	4A	125V
M09A04SM01ST	A Code 4 Pin		1.0	3A	125V
M09A05SM01ST	A Code 5 Pin		1.0	3A	125V
M09A07SM01ST	A Code 7 Pin		0.5	1A	125V
M09A08SM01ST	A Code 8 Pin		0.5	1A	125V

Material:

1. Insulation: PA, Black
2. Connection Nut: Copper Alloy, Plated Nickel
3. Fixed Nut: Copper Alloy, Plated Nickel
4. O-Ring: Rubber, Black
5. Metal Shell: Copper Alloy, Plated Nickel
6. Contact: Copper Alloy, Plated Gold
7. Cable Clamp: PA, Black
8. Pressing Nut: Copper Alloy, Plated Nickel

Technical Data:

1. Standard: -
2. Rated Voltage: See Table 1
3. Rated Current: See Table 1
4. Rated Temperature: -40°C~+85°C
5. Durability: <1000 Times Cycles
6. Insulation Resistance: <100MΩ, 500V/DC
7. Contact Resistance: <10mΩ
8. Protection Degree: IP67 (Correct locking state)
9. Applicable Wire Gauge: 20AWG/0.5mm² Max
10. Packaging: 1 Pcs/Small Bag, 50 Pcs(S PQ)



This drawing contains information that is proprietary to BOMCAN and should not be used without written permission. Powered by bomcan.com

DESCRIPTION	METAL M9 SENSOR CONNECTOR SOCKET FIELD ASSEMBLY				
DWG NO	M09AXXSM01ST	BOMCAN PART No	M09AXXSM01ST		
DRAWN BY	CLARA 2015. 12. 01	CUSTOMER P/N	-		
CHECKED BY	CALEB 2015. 12. 01	SIZE: A4	SHEET	UNIT	SCALE
APPROVED BY	BILL 2015. 12. 01	REV: AA	1 of 1	MM	FREE

