


REV	ECN NO	DESCRIPTION	DATE	APPROVED
AA	-	NEW RELEASED	2020.07.28	CLARA



Electrical specifications:
 Use of voltage range: 300V
 Current range: 5A
 Temperature range: -40°C~+80°C

Material specifications:
 Cable: UL Style Cable PVC or TPU
 Connector: M16 Connector AISG
 Body Shell: Brass with Nickel Plated

Mechanical performance:
 Minimum bending radius: Fixed installation: 8x Cable OD
 Flexible installation: 10x Cable OD

Electrical testing of finished cable:
 100% Open / Short / Miswiring testing
 Insulation resistance: DC300V 10MΩ
 Conductor resistance: 5Ω

Manufacturer: Bomcan.com
Standard: IEC61076-2-106

M16 Cable Assembly Wiring		
M16 Plug Pins	Cable Wiring color	M16 Socket Pins
1	White	1
2	Brown	2
3	Green	3
4	Yellow	4
5	Gray	5
6	Pink	6
7	Blue	7
8	Red	8
Shell	Shield	Shell



UNMARKED TOLERANCES	
DIMENSIONS	TOLERANCE
x.	±1.0
x.x	±0.5
x.xx	±0.25
0 to 500	+15 / -0
< 501	+3% / -0 of length
ANGLES	
x°	±1°



This drawing contains information that is proprietary to BOMCAN and should not be used without written permission. Powered by bomcan.com

DESCRIPTION	M16 8PIN CONNECTOR FIELD INSTALLATION CABLE ASSEMBLY			
DWG NO	M16-8A-CAB	BOMCAN PART No	-	
DRAWN BY	CLARA 2020.07.28	CUSTOMER P/N	-	
CHECKED BY	CALEB 2020.07.28	SIZE: A3	SHEET	UNIT
APPROVED BY	BILL 2020.07.28	REV: AA	1 of 1	mm
		SCALE	Free	Third angle projection