

1		2		3		4		5		Customer drawings			
REV	ECN NO	DESCRIPTION		DATE	APPROVED		RoHS PASS						
AA	-	NEW RELEASED		2017.03.15	CLARA								
<p>Electrical specifications: Use of voltage range: 5V Current range: 2A Temperature range: -20°C~+80°C</p> <p>Material specifications Cable: Type-C Cable Connector: Type-C Connector Overmolding: Black PVC</p> <p>Mechanical properties Minimum bending radius: Fixed installation: 8x Cable OD Flexible installation: 10x Cable OD</p> <p>Electrical testing of finished cable 100% Open / Short / Miswiring testing Insulation resistance: DC300V 10MΩ Conductor resistance: 5Ω</p> <p>Manufacturer: Bomcan</p>													
						This drawing contains information that is proprietary to BOMCAN and should not be used without written permission. Powered by bomcan.com							
DESCRIPTION		USB TYPE C CABLE ASSEMBLY											
DWG NO		-		BOMCAN PART No		TYPE-C							
DRAWN BY		CLARA 2017-03-15		CUSTOMER P/N		-							
CHECKED BY		CALEB 2017-03-15		SIZE		SHEET		UNIT		SCALE		Third angle projection	
APPROVED BY		BILL 2017-03-15		REV		1 of 1		MM		FREE			
1		2		3		4		5		A4			

www.bomcan.com